

### Features :

- Frequency Range: 50/60Hz
- Small volume, light weight, easy to install
- Flexible structure
- Low magnetic leakage, low noise
- Totally external insulation

### Applications :

- Hi Fi and Hi End stereo equipment, DJ stage audio amplifier, karaoke, broadcasting equipment, testing equipment (i.e. instruments), Uninterruptable Power System (UPS), computer peripherals, automatic control system, industrial machine equipment, telecommunications equipment.

### Power Rating : (Unit :mm)



Power Rating VA		Dimensions		Power Rating VA		Dimensions	
		OD	H			OD	H
50VA	1	82	38	600VA	1	135	63
	2	90	33		2	145	58
75VA	1	90	45	750VA	1	138	75
	2	100	36		2	155	65
100VA	1	90	55	900VA	1	145	75
	2	100	45		2	165	65
	3	116	36	1000VA	1	157	70
150VA	1	90	65		2	180	60
	2	100	50	1200VA	1	157	80
	3	125	37		2	173	65
200VA	1	100	60	1400VA	1	176	78
	2	110	50		2	183	65
	3	135	38	1600VA	1	165	80
250VA	1	110	65		2	185	72
	2	116	50	1800VA	1	175	82
	3	145	38		2	185	78
300VA	1	110	65	2000VA	1	180	90
	2	116	55		2	185	85
	3	155	38	2300VA	1	185	95
350VA	1	110	70		2	200	85
	2	118	60	2500VA	1	185	95
	3	165	38		2	200	85
400VA	1	118	67	3000VA	1	203	90
	2	127	57		2	208	85
	3	175	38	3500VA	1	203	100
500VA	1	127	68		2	208	90
	2	135	63	4000VA	1	208	100
	3	180	38		2	223	90

